

CCSE-DL-R Participant device long mic, black

CCS 700



- ▶ Compact, attractive design
- ▶ Built-in volume control for headphones
- ▶ Microphone with flexible stem and light ring
- ▶ Two headphone sockets

The CCS 700 Ultro Discussion System is a suitable for use in meetings and conference venues with a limited number of participants.

The CCSE-DL-R delegate units enable participants to actively take part in the meeting proceedings. A built-in microphone allows them to speak to the other delegates, and they can listen to the discussion using the built-in loudspeaker or (optional) personal headphones.

Functions

Microphone with flexible stem and light ring

The microphone has a flexible stem, which is easily adjustable to suit personal preferences. It also allows two people to use the same delegate unit as they can pull the microphone towards them, when it is required to speak. The microphone is fixed to the base of the delegate unit. Incorporated into the head of the microphone is a light ring which illuminates red when the microphone is on.

Built-in loudspeaker

Loudspeaker volume is set centrally at the control unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on.

Two headphone sockets

Two 3.5 mm stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected so two delegates can simultaneously use the unit.

Built-in volume control for headphones

The headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort.

Controls and Indicators

- Microphone on/off button.
- Rotary volume control for adjusting headphone volume.
- Loudspeaker, automatically muted when microphone is on.
- Microphone 'on' indicator (red LED).
- Light ring indicator on microphone stem, lights up red when microphone is on.

Interconnections

- 1 x 2.7 m cable terminated with an 8-pin male connector for loop-through connection to other delegate or chairperson units.
- 1 x 8-pin circular female connector for loop-through connection to other delegate or chairperson units.
- 2 x 3.5 mm stereo headphone sockets.

Installation/configuration notes

This is a professional product that should be installed, used and maintained by trained professionals only.

Parts included

Quantity	Component
1	CCSE-DL-R Participant device long mic, black

Technical specifications**Electrical**

Nominal acoustic input level (dB SPL)	85 dB SPL
Frequency response (Hz)	400 Hz – 10,000 Hz

Mechanical

Dimensions (H x W x D) (mm) without microphone	54 mm x 136 mm x 138 mm
Microphone stem length (mm)	488 mm
Weight (kg)	1.2 kg
Mounting type	Tabletop
Color	Black

Environmental

Operating temperature (°C)	-5 °C – 45 °C
Storage temperature (°C)	-40 °C – 70 °C

Ordering information**CCSE-DL-R Participant device long mic, black**

Participant device long mic, black base.

Order number **CCSE-DL-R | F.01U.434.026**<https://www.boschsecurity.com>