

CELTO ACOUSTIQUE CT12 G3 2-Way Fullrange Loudspeaker

Perfectly built speaker with high-quality WISA birch plywood





8







List price: on demand €

incl. 19% VAT.

Features:

Logistic

- Horn 90 degree rotatable for horizontal or vertical use
- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- For application areas such as: Concerts/FoH's; Clubs/dancing school; Installation; mobile use; Stage; theater; sports centres/gyms; multi-purpose hall

Technical specifications:

Power:	Rated: 600W AES Program: 1200W Peak: 2400W
Frequency range:	50 - 22000 Hz
Sensitivity:	97 dB
Max. SPL:	131 dB
Dispersion angle:	80° x 50° rotatable horn
Impedance:	8 ohms
Flying points:	17 x M8 thread
Connections:	2 x 4-pol SpeakON mounting version (F)
Crossover frequency:	1500 Hz

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Speaker:	1 x woofer 12" Basket material: aluminum Voice coil lows 3" Diaphragmmaterial: PEEK (H.T. polymer) 1 x Annular compression driver 1" Voice coil annular 1,75"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 35,6 cm Depth: 34,5 cm Height: 62,0 cm
Weight:	22,00 kg