

CELTO ACOUSTIQUE CT15 G3 2-Way Fullrange Loudspeaker

Perfectly built speaker with high-quality WISA birch plywood











List price: on demand €

incl. 19% VAT.

Features:

- Horn 90 degree rotatable for horizontal or vertical use

- With rigging points
- CELTO ACOUSTIQUE driver
- Built with NEUTRIK connector
- For application areas such as: Concerts/FoH's; Clubs/dancing school; Installation; mobile use; Stage; theater; sports centres/gyms; multi-purpose hall

Package contents

1 x top

Technical specifications:

Power:	800W AES Program: 1600W Peak: 3400W
Frequency range:	48 - 22000 Hz
Sensitivity:	98 dB
Max. SPL:	133 dB
Dispersion angle:	80° x 50° rotatable horn
Impedance:	8 ohms
Flying points:	15 x M8 thread
Connections:	2 x 4-pol SpeakON mounting version (F)

Logistic

Eurolite®, Futurelight®, PSSO®, Roadinger®, Alutruss®, Europalms® and Dimavery® are trademarks of Steinigke Showtechnic GmbH, Andreas-Bauer-Straße 5, DE-97297 Waldbüttelbrunn All rights reserved. Subject to change without notice. Errors and omissions excepted.Illustration only. Actual item may differ from photo.

Crossover frequency:	1400 Hz
Speaker:	Woofer 15"
	Basket material: aluminum
	Voice coil lows 3,5"
	Diaphragmmaterial: PEEK (H.T. polymer)
	Annular compression driver 1"
	Voice coil annular 1,75"
Type of speaker:	Compact cabinet speaker
Type of construction:	Vented
Use of brands:	CELTO ACOUSTIQUE driver
	Built with NEUTRIK connector
Material:	Birch multiplex
Color:	Black, textured coating, painted
Dimensions:	Width: 44,5 cm
	Depth: 41,4 cm
	Height: 71,0 cm
Weight:	29,85 kg