

CCSE-CML-R Chairperson device long mic, black

CCS 700



The CCS 700 Ultro Discussion System is a suitable for use in meetings and conference venues with a limited number of participants. The CCSE-CML-R Chairperson devices are equipped with enhanced functionality that enables the user to take the role of chairperson in a conference or meeting. The unit has a fixed microphone with flexible stem. Headphone sockets can be used to listen to the discussion in situations with excessive background noise.

Functions

Priority button for chairperson microphone

In addition to the 'microphone on' button the chairperson units feature a 'chairperson priority' button. When pressed the priority button causes all currently active delegate microphones to be permanently muted.

Optional chime tone facility for preceding chairperson announcements

A sliding switch is available on the rear of CCSE-CU-R which can be used to activate the chime tone to precede chairperson priority calls.

Built-in loudspeaker

Loudspeaker volume is set centrally at the control unit for all delegate units. To prevent acoustic feedback, the built-in loudspeaker is automatically muted when the microphone is on.

Two headphone sockets

- ▶ Priority button for chairperson microphone
- ▶ Optional chime tone facility for preceding chairperson announcements
- ▶ Modern, unobtrusive styling to match the CCSE-DL Delegate Units
- ▶ Microphone with flexible stem and light ring
- ▶ Two headphone sockets

Two 3.5 mm stereo headphone sockets (wired for mono) allow two pairs of headphones to be connected so two delegates can simultaneously use the unit.

Built-in volume control for headphones

The headphone volume level can be adjusted by means of a thumbwheel on the unit for maximum comfort.

Controls and Indicators

- Microphone on/off button.
- Chairperson priority button.
- Rotary volume control for adjusting headphone volume.
- Loudspeaker, automatically muted when microphone is on.
- Microphone 'on' indicator (red LED).
- Light ring indicator on microphone stem, lights up red when microphone is on.

Interconnections

- 1 x 2.7 m cable terminated with an 8-pin male connector for loop-through connection to other delegate or chairperson units.
- 1 x 8-pin circular female connector for loop-through connection to other delegate or chairperson units.
- 2 x 3.5 mm stereo headphone sockets.

Installation/configuration notes

This is a professional product that should be installed, used and maintained by trained professionals only.

Parts included

Quantity	Component
1	CCSE-CML-R Chairperson device long mic, black

Technical specifications**Electrical**

Nominal acoustic input level (dB SPL)	85 dB SPL
Frequency response (Hz)	400 Hz – 10,000 Hz

Mechanical

Dimensions (H x W x D) (mm) without microphone	54 mm x 136 mm x 138 mm
Microphone stem length (mm)	488 mm
Weight (kg)	1.2 kg
Mounting type	Tabletop
Color	Black

Environmental

Operating temperature (°C)	-5 °C – 45 °C
Storage temperature (°C)	-40 °C – 70 °C

Ordering information**CCSE-CML-R Chairperson device long mic, black**

Chairperson device long mic, black base.

Order number **CCSE-CML-R | F.01U.434.028**<https://www.boschsecurity.com>