



**CSW118**

<b>MODEL</b>	CSW118
<b>Speaker type</b>	Multi-purpose vented sub woofer
<b>Power Handling (AES standard)</b>	1500W RMS / 6000W Peak
<b>Nominal impedance</b>	8 ohms
<b>Average sensitivity</b>	97dB / 1W / 1m
<b>Maximum SPL (calculated)</b>	129 dB RMS / 135dB Peak
<b>Frequency response (-6dB no preset)</b>	34~1500Hz
<b>Nominal directivity (-6dB)</b>	Omni in usable range
<b>Cabinet</b>	Exterior grade Birch Plywood Heavily braced with Tongue & Groove
<b>Cabinet finish</b>	Textured Waterborne Black coating Acoustic PU foam behind Front grill
<b>Floor monitor use</b>	N/A
<b>Flying hardware</b>	No
<b>Mounting hardware</b>	2pcs M20 thread socket
<b>LF</b>	18" CELTO ACOUSTIQUE 18SW1500-8
<b>Woofers Chassis</b>	Die Cast Aluminum
<b>Woofers Voice coil diameter</b>	4" / 100mm long throw
<b>HF</b>	N/A
<b>HF RMS power (AES standard)</b>	
<b>HF Exit</b>	
<b>HF Voice coil diameter</b>	
<b>HF Diaphragm</b>	
<b>Crossover</b>	No, active mode only
<b>Connectors</b>	Genuine NEUTRIK 2pcs Speakon NL4MP
<b>Speaker size (HxWxD)</b>	632x570x650 mm
<b>Speaker Weight</b>	44kg
<b>Shipping information</b>	51kg 735x675x750 mm
<b>Accessories</b>	CSW118-SBAG (padded cover bag) CPC-70 (pole bar with crank) SUBWHKIT100C (castor wheel kit)

