



CSW218



MODEL	CSW218
Speaker type	Multi-purpose vented sub woofer
Power Handling (AES standard)	3000W RMS / 12000W Peak
Nominal impedance	4 ohms
Average sensitivity	100dB / 1W / 1m
Maximum SPL (calculated)	135 dB RMS / 141dB Peak
Frequency response (-6dB no preset)	34~1500Hz
Nominal directivity (-6dB)	Omni in usable range
Cabinet	Exterior grade Birch Plywood Heavily braced with Tongue & Groove
Cabinet finish	Textured Waterborne Black coating Acoustic PU foam behind Front grill
Floor monitor use	N/A
Flying hardware	No
Mounting hardware	2pcs M20 thread socket
LF	18" CELTO ACOUSTIQUE 18SW1500-8 (2pcs)
Woofer Chassis	Die Cast Aluminum
Woofer Voice coil diameter	4" / 100mm long throw
HF	N/A
HF RMS power (AES standard)	
HF Exit	
HF Voice coil diameter	
HF Diaphragm	
Crossover	No, active mode only
Connectors	Genuine NEUTRIK 2pcs Speakon NL4MP
Speaker size (HxWxD)	580×1100×740 mm
Speaker Weight	80kg
Shipping information	92kg 680×1200×840 mm
Accessories	CSW218-SBAG (padded cover bag) CPC-70 (pole bar with crank) SUBWHKIT100C (castor wheel kit)