

## Stage Speaker Series

### Features:





- >Elegant appearance, environmental protection water-paint;
- >Wearable, solid, water-proof wooden box
- >High power/sensitivity, sweet tone, rich human voice, powerful bass
- >Over-current protection and PTC protection for HF
- >Twelve M10 flying points for quick set up and adjustment

### Applications:

- >Reinforcement system for touring show, meeting room, multi-purpose hall, bar, club, etc;
- >Auxiliary system in medium/large meeting room, auditorium, etc;



Cutaway view



Model	SX-08	SX-10	SX-112F	SX-115F
Type	2-way 8" full range cabinet	2-way 10" full range cabinet	2-way 12" full range cabinet	2-way 15" full range cabinet
Frequency response	75Hz~20kHz (-10dB)	55Hz~20kHz (-10dB)	50Hz~20kHz (-10dB)	45Hz~20kHz (-10dB)
Sensitivity(1W@1m)	92 dB	94 dB	96 dB	97 dB
Nominal Impedance	8Ω	8Ω	8Ω	8Ω
Power handling	150W (continuous), 600W (peak)	200W (continuous), 800W (peak)	300W (continuous), 1200W (peak)	400W (continuous), 1600W (peak)
Crossover	2.7kHz	2.5kHz	2.5kHz	2.5kHz
LF	8" MF/LF / 50mm voice coil	10" MF/LF / 65mm voice coil	12" MF/LF / 75mm voice coil	15" MF/LF / 75mm voice coil
HF	PEN diaphragm / 34mm voice coil	PEN diaphragm / 34mm voice coil	PEN diaphragm / 44mm voice coil	PEN diaphragm / 44mm voice coil
Coverage(HxV)	90°x40°	90°x40°	90°x60°	90°x60°
Max. SPL	120dB	123dB	127dB	129dB
Weight	11Kg	18.5kg	24.5Kg	32Kg
Dimension(WxHxD)	268x420x247 (mm)	326x484x319 (mm)	379x569x369(mm)	441x666x427(mm)