speakers

www.trungchinhaudio.vn

S115V

15" cast frame woofer " pure titanium diaphragm 90 x 45 degree CD horn ntegral pole socket for stand mounting Excellent for high-level music and vocals

SW118V

·Response down to 30Hz · Efficient Bass reflex design Integral socket for main speaker mounting · Great for use with dance music



18" cast frame driver

SM12V

.12" 2-way floor monitor .15" cast frame driver ·Low profile design ·Long travel for solid Can easily be used as a bass down to 35Hz main speaker Pole socket allows use as a main speaker mounting main speaker Awesome vocal monitor more bass is required

SM15V

.15" 2-way floor monitor · Heavy-duty cast frame woofer ·Very high output Pole socket allows use as a main speaker Ready for use with electronic music

SW115V **SM10V**

Integral socket for

·Appropriate wherever

10" floor monitor 1" titanium dome compression driver 90 x 90 degree dispersion Pole socket allows use as a main speaker Great where size is a concern

Club Series V loudspeakers with the S prefix have rugged carpet covering and steel corner protectors to hold up to the rigors of transport.

Heavy arced steel grilles offer protection for the woofer. Models are available for any application from small speech reinforcement to very

high output dance requirements. No matter which model you choose, years of high performance sound are assured.



*

C112V

12" 2-way design

stand mounting

· Great for vocals

۲

S

E

۲

115VA & C112VA

 Flying versions of C112V and C115V 12 integral fly points erminal strip for easy wiring ·Eye bolts included ·Ready to hang

S112V

·12" high power woofer ·2" titanium compression driver ·Integral pole socket for stand mounting ·Perfect for small bands

CW218V ·Dual 18" subwoofer

S

YAMAHA

E

R

· Unique folded baffle design ·Low-profile cabinet ·Capable of extreme SPL

SW218V

18" subwoofer st frame drivers 2400-watt peak power handling Amazing bass performance

3

S215V ·Dual 15" cast

frame woofers ·2000-watt peak power handling ·Tightly braced cabinet ·Excellent high-output performer

C

L

U

B

club v speakers C SERIES

C215V

- •Two 15" cast frame woofers | 10" floor monitor
- handling
- Perfect where high are required

CM10V

·2000-watt peak power ·1" titanium dome a main speaker sound pressure levels . Pole socket allows use as a main speaker Great where size is a concern

CM12V

.12" 2-way floor monitor ·2" titanium HF driver compression driver · Rugged, low-profile design .90 x 45 degree CD horn . Can also be used as . Pole socket allows use as a main speaker · Great for vocals

CM15V

main speaker

Very high output

·Full frequency response

C115V

- ·15" cast frame woofer
- ·1000 watt peak power handling
- •90 x 45 degree CD horn
- Integral pole socket for
- stand mounting
- Excellent for live and
- recorded music

CW118V

- ·18" cast frame driver
- ·1200 watt peak power handling
- · Bass reflex design
- Integral socket for mai
- speaker mounting Great for use with
- dance music

.15" cast frame driver .15" 2-way floor monitor ·Efficient bass-reflex design · Integral socket for main · Pole socket allows use as a speaker mounting Solid response down to 35Hz

CW115V

æ

Club V loudspeakers with the C prefix are coated with a heavy-duty elastomeric spray coating. Designed as an installation alternative to the carpeted S versions, they can easily fit any décor. The finish is very tough, and readily paintable to match surroundings. The steel grilles are foam-lined with acoustically transparent material to provide a more subdued appearance.

Applications dub v speakers

Club Series loudspeakers, along with Yamaha mixers and amplifiers, were designed to satisfy almost any application. The examples below illustrate how easy choosing the proper system or adding to existing systems can be.

Speech or Vocal Reinforcement System



Dance Band System



House of Worship System



Visit www.yamaha.com/proaudio to explore Yamaha's full line of professional audio equipment.







Y A Model	M A Woofer	н Tweeter	C L U	B Nominal	V S E Power Handling	R Sensitivity	_{E spl} S Maximum	S P Dimensions ²	E C S Weight ²
S SERIES	oad-worthy, rugged	(diaphragm) 2" titanium d carpet covered models	Response (-10dB)	Impedance 8	(noise ¹ /program/peak) 250 / 500 / 1000	1W, 1m 99dB	129	W x H x D 19 x 28 x 15	(pounds) 60.5
S112V	12"	2" titanium	60Hz–16kHz	8	175 / 350/ 700	97dB	126dB	17 x 25 x 13	42.5
S115V	15"		55Hz–16kHz						
S215V	15" (2)	2" titanium	42Hz–16kHz	4	500 / 1000/ 2000	99dB	132	20 x 46 x 24	101.0
SM10V	10"	1" phenolic	70Hz–20kHz	8	125 / 250/ 500	96dB	123	22 x 14 x 11	27.0
SM12V	12"	2" titanium	60Hz–16kHz	8	175 / 350/ 700	97dB	126	25 x 16 x 14	43.0
SM15V	15"	2" titanium	55Hz–16kHz	8	250 / 500 / 1000	99dB	129	28 x 19 x 13	57.0
SW115V	15"	n/a	35Hz–2kHz	8	250 / 500 / 1000	95dB	125	19 x 24 x 21	64.0
SW118V	18"	n/a	30Hz–2kHz	8	300 / 600 / 1200	96dB	127	22 x 32 x 25	71.0
SW218V	18" (2)	n/a	30Hz–2kHz	4	600 / 1200/ 2400	98dB	132	48 x 23 x 26	132.0
C SERIES) Ourable spray-fin	2" titanium ished models with foa	med steel grilles	8	250 / 500 / 1000	99dB	129	19 x 28 x 15	60.5
C112V	12"	2" titanium	60Hz–16kHz	8	175 / 350/ 700	97dB	126	17 x 25 x 13	42.5
C115V	15"		55Hz–16kHz						
C215V	15" (2)	2" titanium	42Hz–16kHz	4	500 / 1000/ 2000	99dB	132	20 x 46 x 24	101.0
CM10V	10"	1" phenolic	70Hz–20kHz	8	125 / 250/ 500	96dB	123	22 x 14 x 11	27.0
CM12V	12"	2" titanium	60Hz–16kHz	8	175 / 350/ 700	97dB	126	25 x 16 x 14	43.0
CM15V	15"	2" titanium	55Hz–16kHz	8	250 / 500 / 1000	99dB	129	28 x 19 x 13	57.0
CW115V	15"	n/a	35Hz–2kHz	8	250 / 500 / 1000	95dB	125	19 x 24 x 21	64.0
CW118V	18"	n/a	30Hz–2kHz	8	300 / 600 / 1200	96dB	127	22 x 32 x 25	71.0
CW218V	18" (2)	n/a	30Hz–2kHz	4	600 / 1200/ 2400	98dB	132	48 x 23 x 26	132.0
FLYABLE MODELS _{15"} Ideal for installations				8	250 / 500 / 1000	99dB	129	19 x 28 x 15	60.5
C112VA	12"	2" titanium	60Hz–16kHz	8	175 / 350/ 700	97dB	126	17 x 25 x 13	42.5
C115VA		2" titanium	55Hz–16kHz						

_

¹ Per IEC RS-426 specifications. ² Dimensions and weight are approximate. ³ Calculated.



© 2004 Yamaha Corporation of America P. O. Box 6600, Buena Park, CA 90622-6600 Yamaha is a registered trademark of Yamaha Corporation. All rights reserved. Specifications are subject to change. WWW.YAMAHA.COM/PROAUDIO







$Y A M A H A C L U B \overline{V}$









Yamaha has a long history of both making and reproducing music. The Club Series V loudspeakers represent the latest in our continuing effort to provide the professional features and sound quality you've come to expect and deserve.

Built in the United States, these loudspeakers are designed to provide years of service. High power handling and excellent response have made Club Series loudspeakers the perfect choice for more than 16 years. Whether playing in a band, DJing, or upgrading the sound system at your church or school, with an expanded lineup of over twenty models to choose from, you're sure to find the right loudspeaker. Have a look at what goes into their construction –

- Cabinets are constructed of high quality particleboard, chosen for its high strength and elasticity, consistent void-free makeup and light weight. Another great benefit of this material is its environmental friendliness. Made from southern yellow pine, this material is both abundant and quickly renewable. Accurate CNC routing machines are used to cut every part, assuring consistency with tolerances of one ten thousandth of an inch. Skilled technicians assemble each cabinet by hand, rejecting any defects. Whether covered in durable carpet or the elastomeric spray coating, heavy steel handles and sturdy pole sockets make moving and positioning easy.
- The drivers, or speakers, in these cabinets are custom made by Eminence Speaker Corporation[®] to Yamaha's exacting tolerances. Woofers share design features like high strength curvilinear cones and Dupont Kapton[™] voice coil formers. Oxygen-free copper voice coils and oversized strontium ferrite magnets are also used to provide high power handling and long life. The 15" and 18" drivers use cast aluminum frames to support the massive magnet structure, eliminate flex and help dissipate heat. The compression driver that generates the high frequency sound uses a pure titanium diaphragm. This 2" dome is one of the largest in its class, allowing for very high output and low distortion without the aid of cooling fluids. It's mated to a 90°x 40° custom designed CD (constant directivity) horn with excellent dispersion and response.
- Crossover networks that divide the signal going to the woofer and compression driver are constructed with oversized coils, high voltage capacitors, and power resistors designed to provide the best possible sound quality and minimize loss. Overload protection is also included to protect the components.
- Connections on these loudspeakers are dual Neutrik Speakon[®] and Switchcraft[®] 1/4" jacks for the highest possible strength and current capacity. Two of each connector make it easy to "daisy chain" speakers.

