



# TZ-S240W & TZ-S60W

## Slim Array Speakers



2-way array Speaker with  
uniform sound pressure

## TZ-S240W Slim Array Speaker

Featuring slim construction, the TZ-S240W-AS is a 2-way array speaker containing 32 speaker elements. The sound source speaker elements are vertically arranged in close proximity to each other, and form a continuous linear sound source, achieving uniform sound pressure with less attenuation due to distance.

The TZ-S240W speaker is of a special design which is ideal for long distance sound transmission applications.

### Key Features

- 2-way speaker, with tweeters aligned at the foreground to the side, enabling less disruption to the sound quality of the woofers while maintaining the unit slim.
  - Narrow and focus directivity, limiting vertical sound dispersion.
  - Resist floor and ceiling-originating reflections, enhancing clarity even in reverberant spaces and other problem environments.
  - Reduces feedback occurrence because volume levels are not extraordinarily high even close to the speakers and makes setting gain levels easier.
  - Internal input overload protection circuitry that protects the unit against extremely high input power levels, depending on the type of uses.
  - Can be conveniently set for high-impedance applications by using the optional MT-S0601 matching transformer when driven with a single amplifier.
  - Include wall mounting brackets that allow wide adjustable pan-angle (180°).
  - Stackable up to 2 units with extension bracket.
- Applications: House of Worship, lecture theatre, multi-purpose hall.



### Accessory



Wall Mount Bracket

### Optional



MT-S0601  
Matching Transformer



SR-EP4  
Extension Plate  
for indoor use



SR-TB4  
Wall Tilt Bracket  
for indoor use



SR-WB4  
Wall Mounting Bracket  
for indoor use



SR-FB4  
Flying Bracket



SR-SA4  
Stand Adapter



SR-FS4  
Floor Stand

## TZ-S60W Slim Array Speaker

TOA TZ-S60W Slim Array Speaker, equipped with nine vertically arrayed 8 cm speaker units, delivers high clarity sound with a 90° horizontal x 0° vertical directivity control. This feature enables it to project clear sound even in rooms with reverberation problem.

Two TZ-S60W can be stacked to improve sound transmission distance and the vertical coverage area. For installation flexibility, both low impedance and high impedance is available by a rotary switch.

### Key Features

- 90° horizontal x 0° vertical directivity control
- Low impedance and high impedance selectable by rotary switch
- Accessory speaker brackets provide installation flexibility
- TZ-S60W x 2pcs can be stacked for wider coverage



### Optional Accessory



HY-S60W  
Stacking Bracket

## Specification

<b>TZ-S240W</b>	
Enclosure	Bass-reflex type
Max Input Power	Continuous : 240 W Program : 480 W
Impedance	8 Ω
Sensitivity	94 dB (1 W, 1 m)
Frequency Response	95 - 20,000 Hz
Crossover Frequency	2.5 kHz
Directivity	Horizontal : 100° Vertical : 5°
Speaker Component	Low Frequency : 10cm (4") cone-type woofer x 8 High Frequency : 2.5cm (1") balanced dome tweeter x 24
Input Connector	M4 screw terminal x 2
Operating Temperature	-10 °C ~ 50 °C
Finish	Enclosure : MDF, white paint Net Grille : Punched steel plate, white paint
Dimensions (W x H x D)	160 (W) x 950 (H) x 262 (D) mm
Weight	17 kg
Accessory	Mounting Bracket x 2
Optional	Flying Bracket : SR-FB4 Wall Tilt Bracket : SR-TB4 Extension Plate : SR-EP4 Wall Mounting Bracket : SR-WB4 Stand Adaptor : SR-SA4 Floor Stand : SR-FS4 Matching Transformer (for high impedance) : MT-S0601

<b>TZ-S60W</b>	
Enclosure	Bass-reflex type
Max Input Power (Low Impedance)	120 W (Continuous pink noise)
Rated Input (High Impedance)	60 W
Rated Impedance	Low Impedance: 8Ω 100V Line: 167Ω (60W), 330Ω (30W), 500Ω (20W), 1kΩ (10W), selectable
Sensitivity	95 dB (1 W, 1 m)
Frequency Response	180 - 15,000 Hz
Connection	Push-in terminals
Directivity Angle	Horizontal : 90° Vertical : 0°
Speaker Component	8cm (3") cone-type x 9
Input Connector	M4 screw terminal x 2
Operating Temperature	-10 °C ~ 50 °C
Impedance Change	Rotary Switch (Selectable)
Finish	Enclosure : MDF, Wet paint, white Punched Net : SECC, Wet paint, white Wall Bracket: SECC, Wet paint, white Side Panel: SECC, Wet paint, white Metal Cover: SECC, Wet paint, white
Dimensions (W x H x D)	100 (W) x 883 (H) x 130 (D) mm
Weight	8.2 kg (Unit only)
Accessory	Speaker bracket x 1pc, Joint bracket x 1pc, Wall bracket x 1pc, Fixing bolt M5x60 x 1pc, Hexagon bolt M6x12 (with plain washer and spring washer) x 2pc, Machine screw M5x15 (with plain washer and spring washer) x 4pc
Optional	HY-S60W: Side Stack Bracket x 2pc Rear Stack Bracket x 1pc

