

PRP-UC15L 15W Speaker Cabinet PROSPERO



The PRP-UC15L is a passive speaker for use with the PRP-UC15L-IP Active IP Speaker in a white wooden enclosure for indoor applications. High-quality 5.2" fullrange speaker unit and wooden cabinet with pilot holes for excellent voice clarity and background music effects. Rear panel comes with two sets of mounting brackets for optional horizontal or vertical wall mounting. Rotatable Bosch logo on front panel, to match different mounting orientations.

Functionality

- Used in conjunction with PRP-UC15-IP active IP speakers to access PROSPERO public broadcasting system through IP network
- Rotatable front panel logo
- Mounting bracket included for horizontal or vertical wall mounting options

Regulatory Information

Declaration of Conformity


Environment


110

China RoHS


Installation/Configuration Instructions

Three views of the speaker:






- Excellent voice clarity and background music effects
- > For use with active IP speakers
- Rotatable logo for horizontal or vertical wall mounting



mm





Rear panel interface:



Connect to IP Speaker

Supplied parts

quantities	modules
1	Wooden speakers
1	user manual
1	RoHS
1	Terminal block (set)

Technical indicators

Electrical parameters

Speakers		
rating	15 W, 8 Ω	
Sensitivity (1 kHz, 1 m)	87 dB	
Maximum sound pressure level (1 kHz, 1 m)	99 dB	
Effective frequency range (-10 dB)	95 Hz-19.5 kHz	
Open angle HxV (-6 dB, 1 kHz)	184° x 170°	
Open angle HxV (-6 dB, 4 kHz)	112° x 35°	


Analog Audio Input	
type	1 x Sub Box Output
connector	1 x Two Pin Phoenix Plug

Frequency Response Curve:



Pointing graphs:

• 1K vertical directivity



Mechanical parameters

speakers	
material	Wooden case, metal mesh
	cover

speakers

Dimensions (HxWxD)	280 mm x 180 mm x 110 mm
weights	2300 g
color	White (RAL 9003)

brackets	
material	metal material
color	Black (RAL9017)
mounting	Wall-mounted, optional landscape or portrait orientation

Environmental parameters

operating temperature	-5℃ - 45°C
storage and transportation temperatures	-40°C - 70°C
relative humidity	<95%

Ordering Information

PRP-UC15L 15W Speaker Cabinet

Passive Speaker, 15W, White Wooden Enclosure, Mounting Bracket Included Order # PRP-UC15L | F.01U.429.440

Vendors.

China. Bosch (Shanghai) Security Systems Co., Ltd. 8th Floor, Building 203, No. 333 Fuquan North Road, Hongqiao LinKong Economic Park, Changning District, Shanghai, China LinKong Economic Park, Changning China Zip code: 200335 Tel: +86 21 2218 1111 Fax: +86 21 2218 2099 www.boschsecurity.com.cn Service e-mail: security@cn.bosch.com