



# TZ-107/207

## Column Speakers



High efficiency, wide frequency range, and powerful input handling

## Description

The column speaker has a sleek and compact design, engineered for efficiency and a broad frequency range with an emphasis on high frequencies. It provide a strong power handling capability ensuring superior performance, while the included bracket allows for versatile mounting in various applications.

## Specifications

Model	TZ-107	TZ-207
Rated Input	10 W (Max. 15 W)	20 W (Max. 30 W)
Rated Impedance	100 V line: Hot 1 k $\Omega$ – black, Com - white	100 V line: Hot 500 $\Omega$ – black, Com - white
Sound Pressure Level	93 dB (1 W, 1 m)	96 dB (1 W, 1 m)
Frequency Response	80 - 20,000Hz	85 – 20,000Hz
Dispersion Angle	Horizontal: 200° (1kHz); 98° (4kHz) Vertical: 110° (1kHz); 26° (4kHz)	Horizontal: 200° (1 kHz); 98° (4 kHz) Vertical: 36° (1 kHz); 39° (4 kHz)
Speaker Component	10cm Core-type x2	10cm Core-type x4
Connection	Speaker cord (2-core cabtyre cord $\varnothing$ 6 mm (0.24"), gray)	
IP Code	IP44	
Finish	Enclosure Case: Extrude Aluminum, black, paint Side Panel: Resin, black, paint Punched Net: Surface tread steel plate, black, paint	
Dimensions	140 (W) x 315 (H) x 140 (D) mm	140 (W) x 560 (H) x 140 (D) mm
Weight	2.2kg	3.8kg
Accessory	Speaker bracket x1, Wall Bracket x1, BH Screw M5x60 FeBlk 3-SEMS x1	

## Application



Church



Mosque



Transportation