

## EC-380 Chime Microphone



## **EC-380 Chime Microphone**

The EC-380 is an uniquely shaped and high quality condenser microphone equipped with a electrical chime and designed for paging applications. With its' adjustable chime volume, flexible power option of battery or DC, the EC-380 is definitely the choice when selecting a hassle-free plug and play chime microphone.





## **Specification**

Specification	
Model	EC-380
Power Source	6V DC (4 x "AA" batteries) or DC adapter (9 - 24V)
Current Consumption	13mA during chime and 6mA microphone operation
Microphone Element	Condenser
Polar Pattern	Cardioid
Chime Tones	4-Tone Chime (Up/Down)
Rated Impedance	600Ω, Balanced
Output	Microphone: -41dB ± 3dB (1 kHz 0dB=1V/Pa)
	Chime Tones: -31dB ± 3dB (maximum position)
Frequency Response Mic.	50 Hz - 18 kHz
Output Connector	XLR-3-32 Equivalent RJ45: Audio output, power supply and contact output
Operating Temperature	0 C - 40 C (32 F - 104 F)
Finish	Stand Mic: ABS Resin, Black, Paint Mic Shaft: Copper alloy, Black, Paint
Dimensions	110 (W) x 145 (D) x 532 (H) mm (4.3" x 5.7" x 20.9")
Weight	558g (exclude batteries)
Accessory	Windscreen x 1, XLR Cable Stereo Phone Plug (7.5m) x 1
Optional Accessory	AD-246 AC Adapter

Note: AC Adapter and Batteries are not supplied with the unit



