

## Powerful Sound Output with Outstanding Clarity

From solo entertainers to touring bands, jazz clubs to houses of worship, for any situation that needs a quality sound system, YamahaÃs A Series speakers are worth a good look and listen. In addition to sounding superb and being capable of handling serious power, these speakers are light, compact and easily manageable when the system needs to be moved or reconfigured. They feature durable metal handles that will withstand nightly transportation, and are pole-mountable for optimum positioning in any room.

Robust carpet covering and metal grilles are pluses, too, minimizing damage while looking downright handsome. But, of course, practicality isnAt the only issue.

You want great sound, too. The A Series speakers feature optimally matched high-power woofers, compression drivers, and constant-directivity horns that deliver your sound to every corner of the room with every subtle nuance intact. ThereÃs also a range of five models to choose from, so you can create the system that is perfect for your touring or installation needs. One possible system is shown in the example below: a pair of A15 and A15WÃs for the house and a pair of A12MÃs on the floor or wherever you need them to hear precisely what youÃre playing or singing.

\*Some models may not be available in all areas.


## GENERAL SPECIFICATIONS

|                         |        |   |  |   |  | -  |
|-------------------------|--------|---|--|---|--|--|
| Model                   |        | A15   | A12  | A10   | A12M   | A15W   |
| Туре                    |        | 2-way bass reflex                                   |  |   |  | bass reflex                                      |
| Frequency range (-10dB) |        | 65Hz-20kHz  | 65Hz-20kHz                                       | 65Hz-20kHz  | 65Hz-20kHz                                       | 50Hz-200Hz                                       |
| Nominal coverage        |        |   | 90H x 40V  |   | 40H x 90V  | -  |
| Nominal Impedance       |        | 8Ω  | 8Ω   | 8Ω  | 8Ω   | 8Ω   |
| Power rating            | NOISE* | 200W  | 150W   | 125W  | 150W   | 250W   |
|                         | PGM    | 400W  | 300W   | 250W  | 300W   | 500W   |
|                         | MAX    | 800W  | 600W   | 500W  | 600W   | 1000W  |
| Sensitivity (1w, 1m)    |        | 98dB SPL  | 97dB SPL   | 98dB SPL  | 97dB SPL   | 97dB SPL   |
| Component               | LF     | 15" cone  | 12" cone   | 10" cone  | 12" cone   | 15" cone   |
|                         | HF     | 1" VC, Horn-TW                                      | 1" VC, Horn-TW                                   | 1" VC, Horn-TW                                      | 1" VC, Horn-TW                                   | -  |
| Connectors              |        | Speakon x 1, Phone x 1                              | Speakon x 1, Phone x 1                           | Speakon x 1, Phone x 1                              | Speakon x 1, Phone x 1                           | Speakon x 2, Phone x 2                           |
| Pole mount socket       |        | 35 mm   | 35 mm  | 35 mm   | 35 mm  | 35 mm  |
| Dimension (W x H x D)   |        | 470 x 665 x 375<br>(18-1/2" x 26-3/16" x 14-13/16") | 405 x 575 x 323<br>(15-7/8" x 22-5/8" x 12-3/4") | 385 x 535 x 307<br>(15-3/16" x 21-1/16" x 12-1/16") | 575 x 405 x 323<br>(22-5/8" x 15-7/8" x 12-3/4") | 485 x 622 x 485<br>(19-1/8" x 24-1/2" x 19-1/8") |
| Weight                  |        | 21.3Kg (46.9 lbs.)                                  | 16Kg (35.3 lbs.)                                 | 14.4Kg (31.7 lbs.)                                  | 15.6Kg (34.4 lbs.)                               | 20.9Kg (46.1 lbs.)                               |


\* EIA RS426


DIMENSIONS






A15







A12









unit : mm

A10








323

ŀ

A12M







A15W